

Laser safety curtain isoPROTECT HIGHTECH in mobile frame - width 2100 adjustable height, Color: black

Product information:

Item no.: 220-HIGH-G-H-2100-01



Laser safety curtain isoPROTECT-Budget in mobile frame, height adjustable, suitable for all wavelengths from 180-11000 nm

Properties:

- Curtain color: black
- Curtain covering area : 2100 x 1800 mm (width x height)
- Tolerance: +/- 25 mm
- Material: isoPROTECT-HighTech
- material thickness: approx. 1,8 mm
- completely assembled with eyelets
- Velcro and loop tape for laser-safe connection of the protective systems - optional at extra charge
- tested according to **DIN EN ISO 25980:2014**
- classified in fire protection class B1 (flame retardant) according to **DIN 4102-4:2016-5**

Power densities according to **EN 12254**:

180-315	100 sec	1MW/m ² (100 W/cm ²)
>315-1050	100 sec	10MW/m ² (1 kW/cm ²)
>1050-1400	100 sec	25MW/m ² (2.5 kW/cm ²)
>1400-11000	100 sec	1MW/m ² (100 W/cm ²)

Mobile frame:

- Width center section: approx. 2150 mm,
- **Possibility to add 2 swivel arms left and right, length each 700 mm or 1100 mm (not included)**
- Adjustable hight from **2100** mm to **2600** mm
- Swiveling: 360 °, freely movable, standard 4 swivel castors, 2 swivel castors with brake and 2 without
- Castor diameter: 75 mm
- Material: steel tubes and profiles
- round tube diameter: 35 x 2,5 mm
- square profile: 50 x 30 x 2 mm

Color: gray powder coated, RAL 7035

incl. metal hooks

Delivery as kit